

# Accu1 9300

## Insulation Blowing Machine



*Shown with optional wireless remote*

The Accu1 9300® is a portable, all fiber, blowing and spraying machine, engineered with the busy contractor in mind. The variable speed blower and adjustable material feed provide powerful, efficient operation with maximum production from a 115-volt machine. Durable construction and corrosion resistant coating provide long life with minimal maintenance.

### Production Rates

Cellulose: 2800 lbs/hr  
Fiberglass: 1000 lbs/hr  
Rockwool: 1600 lbs/hr

### Specifications

- Weight: 290 lbs
- Dimensions: 22" W x 28" D x 63" H
- Hopper Capacity: 14 cu. ft.
- Airlock: 7" x 21" diameter
- Blower Size: Single 13.9A Blower motor
- Power requirements: Dual input, 15 amp/115V/60 Hz (230V/50Hz, CE configuration available)
- Hose: 3" diameter

### Features

- Modular component design
- Welded steel construction with powder coated finish
- Recessed control panel
- 1½ hp TEFC drive motor
- Limited moving parts
- Volt-meter
- Circuit Breaker protection
- Emergency Stop
- Control Panel Override Switch

### Benefits

- Quick part replacement and routine maintenance
- Resists damage and corrosion
- Avoids unintended power shut downs
- Processes the toughest blowing materials
- Reduced frequency of breakdowns and downtime
- Helps monitor machine operation
- Protects electrical components
- Operator safety
- Ability to finish jobs if component fails